



## Linde E16L-01

(ET1661 )

<b>Brand</b>	Linde
<b>Model</b>	E16L-01
<b>Capacity (kg)</b>	1600
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	2790
<b>Height (mm)</b>	1970
<b>Masttype</b>	Duplex
<b>Free lift (mm)</b>	1500
<b>Fork length (mm)</b>	1200
<b>Fork carriage width (mm)</b>	980
<b>Length to fork face (mm)</b>	2062
<b>Width (mm)</b>	1090
<b>Drive wheels (size)</b>	18x7x8
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	15x4,5x8
<b>Type of tyres, steering wheels</b>	Superelastic
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2 x 4,6kw + 10kw
<b>Transmission</b>	Linde digital control
<b>Operation</b>	2 pedalsystem, joystick i kryds
<b>Driver's place</b>	Open cabin
<b>Battery</b>	48v 775ah med central vandpåfyldning
<b>Lights</b>	Work lights
<b>Equipment</b>	forkposition/sideshift
<b>Cabin equipment</b>	Front-, tag- og bagrude
<b>Dead weight (kg)</b>	2005kg+bat
<b>Approved</b>	This machine is delivered with new statutory safety approval