# EP TVL182 Li-Ion

(ET0418(48) )

| | |
|---|---|
| **Brand** | EP |
| **Model** | TVL182 Li-Ion |
| **Type** | Electric 3-wheel forklift |
| **Capacity (kg)** | 1800 |
| **Load centre distance (mm)** | 500 |
| **Lift height (mm)** | 4800 |
| **Height (mm)** | 2160 |
| **Masttype** | Triplex frisigt m/fuld friløft |
| **Free lift (mm)** | 1525 |
| **Length to fork face (mm)** | 2025 |
| **Fork length (mm)** | 1200 |
| **Width (mm)** | 1076 |
| **Drive wheels (size)** | 18x7-8 |
| **Type of tyres, drive wheels** | Superelastic |
| **Steering wheels (size)** | 140/55x9 |
| **Energy** | AC 3-phase |
| **Engine type** | 2X5 kW + 16 kW |
| **Battery** | 80V/150Ah Li-Ion |
| **Charger** | 80V/35A integreret lader |
| **Transmission** | Tranistor control |
| **Equipment** | Friløft, 4 ventiler, Cascade gaffelflytter/sideskift |
| **Driver's place** | Open cabin |
| **Cabin equipment** | Kop- og dokumentholder, aflæggerrum, indstillelig rat, multidisplay LCD |
| **Lights** | Lys til kørsel på vej, BlueSpot, blitz |




| | |
|---|---|
| **Fork carriage width (mm)** | 1040 |
| **Gangbreddebehov / AST (mm)** | 3446 |
| **Venderadius (mm)** | 1641 |
| **Operation** | Joystick eller fingertip samt frem/bak i armlæn |
| **Approved** | This machine is delivered with new statutory safety approval |