

# Manitou 280TJ ST5 S1

(EN1338 )

Test

<b>Brand</b>	Manitou
<b>Model</b>	280TJ ST5 S1
<b>Type</b>	Bomlift
<b>Capacity (kg)</b>	240/350
<b>Working height (mm)</b>	27750
<b>Platform height (mm)</b>	25750
<b>Height (mm)</b>	2710
<b>Width (mm)</b>	2480
<b>Platform width (mm)</b>	2300
<b>Length (mm)</b>	11360 / 8090
<b>Platform length (mm)</b>	900
<b>Ground clearance at centre of wheelbase (mm)</b>	410
<b>Type of tyres, drive wheels</b>	Foam-filled
<b>Energy</b>	Diesel
<b>Engine type</b>	Yanmar 4TNV88C 46HP /34,30kw
<b>Transmission</b>	Hydrostatisk fremdrift 4WD
<b>Equipment</b>	230V til kurv, kontinuerlig rotation, safe man system
<b>Drive speed (km/t)</b>	4,5 / 0,8
<b>Lights</b>	Rotorblink
<b>Outreach (mm)</b>	21450
<b>Dead weight (kg)</b>	16500
<b>Turret rotation</b>	360
<b>Platform rotation</b>	180
<b>Approved</b>	This machine is delivered with new statutory safety approval



<b>Gradeability (%)</b>	40
<b>Styring</b>	4 hjuls styret

Test