

# EP EFL25 PRO

(ET0225 )

<b>Brand</b>	EP
<b>Model</b>	EFL25 PRO
<b>Type</b>	Electric 4-wheel forklift
<b>Capacity (kg)</b>	2500
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4800
<b>Height (mm)</b>	2265
<b>Masttype</b>	Triplex
<b>Free lift (mm)</b>	1555
<b>Length to fork face (mm)</b>	2540
<b>Fork length (mm)</b>	1200
<b>Width (mm)</b>	1154
<b>Drive wheels (size)</b>	7.00x12
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	6.00x9
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	15kW+30kW PMSM (Permanent Magnet Synchronous Motor)
<b>Battery</b>	80V/280Ah lithium*
<b>Charger</b>	80V/35A integreret + 80V/150A ekstern lader
<b>Transmission</b>	Tranistor control
<b>Equipment</b>	4 ventiler m/slangeføring, gaffelflytter/sideskift
<b>Driver's place</b>	Open cabin
<b>Cabin equipment</b>	Grammer komfortsæde, justerbar ratstamme, spejl, elektrisk p-bremse (auto stop), stor fodrum/indstigning (524 mm), multifunktions touch display; vægt- og højdemåler samt mastens tiltvinkel***
<b>Lights</b>	Road light, additional LED work light, flash lamp, bluespot, rear light



<b>Fork carriage width (mm)</b>	1040
<b>Drive speed (km/t)</b>	19/20
<b>Lifting speed m/s</b>	0,55/0,58
<b>Operation</b>	Retningsvælger i armlæn, 2 x joystick i kryds som Linde (kan også leveres med fingertip)
<b>Hydraulik</b>	Lydsvag skruepumpe, 35L pr. minut
<b>Dead weight (kg)</b>	4450

Test