

EP EFL25 PRO

(ET0225-K)

Brand	EP
Model	EFL25 PRO
Capacity (kg)	2500
Load centre distance (mm)	500
Lift height (mm)	4800
Height (mm)	2265
Masttype	Triplex
Free lift (mm)	1555
Fork length (mm)	1200
Length to fork face (mm)	2540
Width (mm)	1154
Drive wheels (size)	7.00x12
Type of tyres, drive wheels	Superelastic
Steering wheels (size)	6.00x9
Energy	AC 3-phase
Engine type	15kW+30kW PMSM (Permanent Magnet Synchronous Motor)
Transmission	Tranistor control
Driver's place	Lukket kabine med varme
Battery	80V/280Ah lithium*
Charger	80V/35A integreret + 80V/150A ekstern lader
Lights	Road light, additional LED work light, flash lamp, bluespot, rear light
Equipment	4 ventiler m/slangeføring, gaffelflytter/sideskift
Cabin equipment	Varme, Grammer luftaffjedret førersæde, højde-display, panorama glastag, vægtsystem



Fork carriage width (mm)	1040
Operation	Retningsvælger i armlæn, 2 x joystick i kryds som Linde (kan også leveres med fingertip)
Drive speed (km/t)	19/20
Lifting speed m/s	0,55/0,58
Dead weight (kg)	4450
Hydraulik	Lydsvag skruerpumpe, 35L pr. minut

Test