

# Manitou 180ATJ 2E3

(EN1379)

|   |  |
|---|--|
| <b>Brand</b>  | Manitou  |
| <b>Model</b>  | 180ATJ 2E3   |
| <b>Type</b>   | Bomlift  |
| <b>Capacity (kg)</b>                                | 230  |
| <b>Working height (mm)</b>                          | 18190  |
| <b>Lift height (mm)</b>                             | 16190  |
| <b>Height (mm)</b>                                  | 2700   |
| <b>Length (mm)</b>                                  | 8500   |
| <b>Platform length (mm)</b>                         | 800  |
| <b>Width (mm)</b>                                   | 2400   |
| <b>Ground clearance at centre of wheelbase (mm)</b> | 430  |
| <b>Drive wheels (size)</b>                          | 20   |
| <b>Type of tyres, drive wheels</b>                  | Foam-filled  |
| <b>Steering wheels (size)</b>                       | 20   |
| <b>Energy</b>                                       | Diesel   |
| <b>Engine type</b>                                  | Kubota   |
| <b>Transmission</b>                                 | Hydrostatisk fremdrift 4WD                                   |
| <b>Turret rotation</b>                              | 360  |
| <b>Platform rotation</b>                            | 180  |
| <b>Tilt jib (grader)</b>                            | 140  |
| <b>Drive speed (km/t)</b>                           | 4,7  |
| <b>Gradeability (%)</b>                             | 40   |
| <b>Lights</b>                                       | Rotorblink   |
| <b>Approved</b>                                     | This machine is delivered with new statutory safety approval |

|                   |         |
|-------------------|---------|
| <b>Wheel (mm)</b> | 12.5-18 |
|-------------------|---------|