

EP RTF25-4L1-HV

(ET1959)

DKK 0,00

Excl. VAT and delivery costs

Brand	EP
Model	RTF25-4L1-HV
Capacity (kg)	2500
Load centre distance (mm)	500
Lift height (mm)	4300
Height (mm)	2220
Masttype	Triplex fuld friløft
Free lift (mm)	1381
Fork length (mm)	1200
Length to fork face (mm)	2958
Width (mm)	1450
Drive wheels (size)	280/80R20
Type of tyres, drive wheels	Pneumatic
Steering wheels (size)	27x10-12
Energy	Electric
Engine type	30kW (for) + 15kW (bag) + 22.4kW (hydraulik) PMSM motorer
Transmission	Trindløst transistorstyring
Driver's place	Lukket kabine med varme samt visker/vasker anlæg
Battery	307V/150Ah lithium
Charger	Integreret oplader
Lights	Lys til kørsel på vej, ekstra LED- lys på mast, baklys, BlueSpot for og bag, blitzlampe
Equipment	Cascade gaffelflytter/sideskift
Cabin equipment	Multifunktions display (batteriindikator, kørehastighed, styrehjulsindikering m.m.), bakkamera, Grammer msg65-531 førersæde, varme, indvendigt spejl, opbevaringsrum i armlæn med USB-stik

Fork carriage width (mm)	1038
Operation	Fingertip og retningsvælger i armlæn
Dead weight (kg)	5500
Ground clearance at centre of wheelbase (mm)	2580
Gradeability (%)	50
Note	Kan også leveres med græsdæk
Approved	This machine is delivered with new statutory safety approval