

# Linde E16P (386)-02

(ET1980 )

<b>Brand</b>	Linde
<b>Model</b>	E16P (386)-02
<b>Capacity (kg)</b>	1600
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4100
<b>Height (mm)</b>	1946
<b>Masttype</b>	Triplex fuld friløft
<b>Free lift (mm)</b>	1344
<b>Length to fork face (mm)</b>	2200
<b>Width (mm)</b>	1100
<b>Drive wheels (size)</b>	180/70-8
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	150/75-8
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2x5KW+11KW
<b>Transmission</b>	Linde digital control
<b>Driver's place</b>	Lukket kabine med varme
<b>Lights</b>	Arbejdslys, BlueSpot bag, blitzlampe
<b>Equipment</b>	4 valve, sideshift
<b>Cabin equipment</b>	-

<b>Fork length (mm)</b>	1200
<b>Operation</b>	Joystick i armlæn
<b>Battery</b>	48V/625Ah
<b>Approved</b>	This machine is delivered with new statutory safety approval