

# Manitou 200ATJ

(EN1389)

<b>Brand</b>	Manitou
<b>Model</b>	200ATJ
<b>Type</b>	Bomlift
<b>Capacity (kg)</b>	230
<b>Working height (mm)</b>	20350
<b>Height (mm)</b>	2700
<b>Platform height (mm)</b>	18350
<b>Length (mm)</b>	8500
<b>Width (mm)</b>	2470
<b>Drive wheels (size)</b>	20
<b>Type of tyres, drive wheels</b>	Foam-filled
<b>Steering wheels (size)</b>	20
<b>Energy</b>	Diesel
<b>Transmission</b>	Hydrostatisk fremdrift 4WD
<b>Outreach (mm)</b>	12000
<b>Udlægshøjde (mm)</b>	8000
<b>Turret rotation</b>	360
<b>Platform rotation</b>	180
<b>Tilt jib (grader)</b>	140
<b>Dead weight (kg)</b>	10050
<b>Approved</b>	This machine is delivered with new statutory safety approval

<b>Platform length (mm)</b>	800
<b>Platform width (mm)</b>	2100
<b>Ground clearance at centre of wheelbase (mm)</b>	430
<b>Styring</b>	4 hjuls styret
<b>Drive speed (km/t)</b>	0,8 / 4,8
<b>Gradeability (%)</b>	40