

# Manitou 260TJ

(EN1390 )

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| Brand                       | Manitou                                                         |
| Model                       | 260TJ                                                           |
| Type                        | Bomlift                                                         |
| Capacity (kg)               | 400                                                             |
| Working height (mm)         | 25890                                                           |
| Platform height (mm)        | 23890                                                           |
| Width (mm)                  | 2480                                                            |
| Platform width (mm)         | 2300                                                            |
| Length (mm)                 | 7880                                                            |
| Platform length (mm)        | 900                                                             |
| Type of tyres, drive wheels | Foam-filled                                                     |
| Energy                      | Diesel                                                          |
| Engine type                 | Yanmar 46hk                                                     |
| Transmission                | Hydrostatisk fremdrift 4WD                                      |
| Equipment                   | 230V til kurv, kontinuerlig rotation, safe man system, spildkit |
| Outreach (mm)               | 19700                                                           |
| Dead weight (kg)            | 16400                                                           |
| Turret rotation             | 360                                                             |
| Platform rotation           | 180                                                             |
| Tilt jib (grader)           | 133                                                             |
| Approved                    | This machine is delivered with new statutory safety approval    |

|                                              |                |
|----------------------------------------------|----------------|
| Ground clearance at centre of wheelbase (mm) | 420            |
| Wheel (mm)                                   | 1025 x 365     |
| Drive speed (km/t)                           | 4,5            |
| Gradeability (%)                             | 40             |
| Styring                                      | 4 hjuls styret |