

# EP TVL182 Li-Ion

(ET0418(55) )

|                             |                                                                                                   |
|-----------------------------|---------------------------------------------------------------------------------------------------|
| Brand                       | EP                                                                                                |
| Model                       | TVL182 Li-Ion                                                                                     |
| Capacity (kg)               | 1800                                                                                              |
| Load centre distance (mm)   | 500                                                                                               |
| Lift height (mm)            | 5500 FF                                                                                           |
| Height (mm)                 | 2395                                                                                              |
| Masttype                    | Triples frislgt m/fuld friløft                                                                    |
| Free lift (mm)              | 1760                                                                                              |
| Fork length (mm)            | 1200                                                                                              |
| Length to fork face (mm)    | 2025                                                                                              |
| Width (mm)                  | 1076                                                                                              |
| Drive wheels (size)         | 18x7-8                                                                                            |
| Type of tyres, drive wheels | Non-marking superelastic                                                                          |
| Steering wheels (size)      | 140/55x9                                                                                          |
| Energy                      | AC 3-phase                                                                                        |
| Engine type                 | 2X5 kW + 16 kW                                                                                    |
| Transmission                | Tranistor control                                                                                 |
| Driver's place              | Open cabin                                                                                        |
| Battery                     | 80V/150ah litium                                                                                  |
| Charger                     | 80V/35A integreret lader                                                                          |
| Lights                      | Lys til kørsel på vej, BlueSpot, blitz                                                            |
| Equipment                   | Friløft, 4 ventiler, Cascade gaffelflytter/sideskift                                              |
| Cabin equipment             | Kop- og dokumentholder, aflæggerum, indstillelig rat, multidisplay LCD, Grammer MSG65 komfortsæde |



|                            |                                                              |
|----------------------------|--------------------------------------------------------------|
| Fork carriage width (mm)   | 1040                                                         |
| Gangbreddebehov / AST (mm) | 3446                                                         |
| Venderadius (mm)           | 1641                                                         |
| Operation                  | Joystick eller fingertip samt frem/bak i armlæn              |
| Approved                   | This machine is delivered with new statutory safety approval |