

EP RSL16i PRO MAX (55)

(ES1892)

DKK 0,00

Excl. VAT and delivery costs

Brand	EP
Model	RSL16i PRO
Capacity (kg)	2000/1600
Load centre distance (mm)	600
Lift height (mm)	5500
Height (mm)	2385
Free lift (mm)	2000
Fork length (mm)	1150
Fork measurements (mm)	65x170x1150
Length to fork face (mm)	971
Width (mm)	850
Masttype	Triplex
Energy	AC 3-phase
Engine type	4,5kw + 3kw
Transmission	Tranistor control
Drive wheels (size)	230x70
Type of tyres, drive wheels	Polyurethane
Battery	24V/205Ah Li-Ion
Charger	Li-Ion 24V/100A (fuld opladning af batteri på 2 timer via ladestik i siden)
Driver's place	Driver platform
Equipment	Initial-, proportional- samt friløft, el-servo, komfort førerplatform, USB-stik på instrumentbord, hastighedsreduktion når man drejer samt ved fuld løftehøjde
Warranty	12 måneders fabriksgaranti



AST mål (arbejdsgang bredde)	2602
Fork carriage width (mm)	570
Initialløft (mm)	120
Drive speed (km/t)	9/11
Lifting speed m/s	0,23/0,3
Sænkehastighed m/s	0,4/0,36
Note	Kapacitet: 2000 kg på initialløft/benene - 1600 kg på gaflerne