

# Linde E18-02

(ET2007 )

|                             |                                     |
|-----------------------------|-------------------------------------|
| Brand                       | Linde                               |
| Model                       | E18-02                              |
| Capacity (kg)               | 1800                                |
| Load centre distance (mm)   | 500                                 |
| Lift height (mm)            | 5475                                |
| Height (mm)                 | 2472                                |
| Masttype                    | Triplex                             |
| Free lift (mm)              | 1869                                |
| Length to fork face (mm)    | 2000                                |
| Width (mm)                  | 1150                                |
| Drive wheels (size)         | 200/50x10                           |
| Type of tyres, drive wheels | Superelastic                        |
| Steering wheels (size)      | 140/55-9                            |
| Energy                      | AC 3-phase                          |
| Engine type                 | 2x5KW+11KW                          |
| Transmission                | Linde digital control               |
| Driver's place              | Open cabin                          |
| Lights                      | Work lights, blue spot              |
| Equipment                   | 4 ventiler, gaffelflytter/sideskift |
| Cabin equipment             | Mirror                              |

|                          |                                                              |
|--------------------------|--------------------------------------------------------------|
| Fork length (mm)         | 1200                                                         |
| Fork carriage width (mm) | 980                                                          |
| Battery                  | 48V/625ah                                                    |
| Approved                 | This machine is delivered with new statutory safety approval |